

CORONA TREATMENT FOR MONOLAYER FILM PLANT



EL-MONOCOR



**ELTECH
ENGINEERS PVT LTD**

We treat anything...

Since 1992

30
YEARS
OF EXCELLENCE IN CORONA
PLASMA
STATIC

CORONA TREATMENT FOR MONOLAYER FILM PLANT

Eltech manufactures best quality corona treater for monolayer film plant extruder and this film is formed by mixing polypropylene or polyethylene(structural material) with vinyl-acetate or methacrylate(printable material). This forms the unitary mixture. Then the mixture is extruded and heated.



**ELTECH
ENGINEERS PVT LTD**

We treat anything...

Since 1992

30
YEARS
OF EXCELLENCE IN CORONA
PLASMA
STATIC



Technical Specifications

- Input Supply : 415 V AC, $\pm 5\%$, 3 Φ , 4 Wire - monolayer
- Treatment Size : 300-2000 mm
- Line Speed : 0-50 meter/min
- Material: Non Conductive
- Treating Sides : Single / Double
- Input Frequency : 50 Hz
- Output Frequency : 20-50 KHZ
- Approx Output Power (KW) : 0.5 KW - 2 KW
- Maximum Temperature : 0 ~ 50 Degree celsius
- Blower: 1 H.P
- Treatment Electrode : Multisegmented
- Dynes Level : 38-48 Dynes/cm
- Length of HV Cable : 2.5 Mtr
- Corona Output : Ultra high frequency using latest IGBT technology, Constant at same speed, No influence of supply voltage, Accurate output power.
- Certifications : CE , RoHs , ISO



**ELTECH
ENGINEERS PVT LTD**

We treat anything...

Since 1992

30
YEARS

OF EXCELLENCE IN

CORONA
PLASMA
STATIC

Features

- Ultra High Frequency using the latest IGBT technology.
- Indication of Corona Current.
- Balanced rollers.
- Corona Treater rollers covered with high dielectric grade sleeve.
- Prevent premature failure of roller bearing by having a proper grounding system.
- Pneumatic Operated Corona Treatment Station for material feeding.
- Even Suction throughout the treatment station helps to extract Ozone efficiently.
- Cooling provided by the Blower prevents wrapping of electrodes and helps to achieve a Consistent Treatment Level.
- Using Forced Convection inside the panel prevents overheating of Electronic Components.
- Providing a Proximity Sensor for detecting Zero Speed which automatically shuts down the power supply when the web achieves low line speed.
- Oil Cooled Transformer for better stability at high temperatures and has excellent electrical insulating properties.
- Easy view window for a clear view of Corona Discharge.

Electronic Protection Features

- Door Open
- MCB protection
- Single Phasing
- Audio/Visual Alarm
- Electronic Overload Trip
- Thermal trip for heatsink
- Under voltage / Over voltage
- Ozone extraction overload trip

Benefits

- Soft start
- Easy to Install
- Easy to maintain
- Customized Design
- Maximum Operator safety
- Compact Simple Construction
- Cost Efficient Treatment Process
- Forced cooled convertor for longer life
- Ultra high frequency using latest IGBT technology

30
YEARS
OF EXCELLENCE IN | CORONA
PLASMA
STATIC



ELTECH ENGINEERS PVT LTD

We treat anything...

Since 1992



A-108, Diamond Industrial Estate, Ketkipada Road, Near Toll Naka,
Dahisar East, Mumbai, Maharashtra - 400068,
Email: info@eltech.in, Mobile : +91-9619686917